

Interior Maintenance:

Proper interior care is essential to the longevity of your restroom trailer. Cleaning products need to be carefully chosen based on their recommended use. Do not use any harsh cleaning products and none containing bleach or ammonia. Never use a hose or pressure washer inside your trailer as this may cause unintended damage.

It is best to begin cleaning at the ceiling and work your way down. Using your multipurpose cleaner and a rag, spray the ceiling, walls, and partitions with a misting of cleaner and wipe down. Also be sure to clean the inside of the doors, the door pulls and the deadbolts.

Use a glass/multi-surface cleaner to clean the vanities, countertops, sinks, faucets, and mirrors. Important note to spray the cleaner on the rag and not let the cleaner seep behind the mirror when cleaning them.

Some like to clean the interior of the toilets and urinals using a wand style cleaner with disposable pads.

The following is from the toilet instruction manual:

For routine cleaning, use SeaLand® Toilet Bowl Cleaner. If this cleaner cannot be found in your area, contact Dometic for your nearest dealer. If the cleaner is not available, use most any non-abrasive bathroom and toilet bowl cleaner. Please follow label instructions.

FLUSH BALL CLEANING: After a period of time, mineral deposits from hard water may build up on the flush ball or seal, resulting in a slow water leak. To prevent this, periodically clean the flush ball and seal.

1. Remove minor debris from the flush ball and seal by slowly pressing and releasing the flush pedal several times. This will loosen and rinse debris from the surfaces. Repeat several times for stubborn buildup.
2. If step 1 does not fully clean the ball and seal, clean with a soft bristle brush and SeaLand Toilet Bowl Cleaner. Turn off water supply to toilet. Fully clean the top of the flush ball and under the seal where it contacts the flush ball.
3. After cleaning underside of seal, apply light downward pressure to top of seal while brushing around full perimeter of seal.
4. Turn on water supply. Press flush lever to open flush ball, and use brush and water to rinse away cleanser and loosened deposits.

Use a disinfectant spray and a rag to clean the toilet seats, and the outside of the toilet bowls and urinals. Make sure to clean the top of the seat and then the bottom, and to clean behind the toilet base shroud.

Clean the floors by first sweeping with a soft bristle broom and then a wet "mop" like a Swiffer WetJet or the like. Lastly, look around the trim at the floor and wall joint and wipe with a rag if necessary.